

Article 13. Floodplain Management Ordinance

ARTICLE I - GENERAL PROVISIONS.....	2
Section 1.1 – Statutory Authorization and Purpose	2
Section 1.2 – Applicability	3
Section 1.3 - Compliance and Liability	3
Section 1.4 – Records	3
Section 1.5 - Abrogation and Greater Restrictions	3
Section 1.6 - Severability.....	3
Section 1.7 - Penalty for Violations.....	4
ARTICLE II - ADMINISTRATION.....	5
Section 2.1 - Designation of the Floodplain Administrator.....	5
Section 2.2 - Duties and Responsibilities of the Floodplain Administrator	5
Section 2.3 - Use and Interpretation of FIRMS.....	7
Section 2.4 - Jurisdictional Boundary Changes	8
Section 2.5 - District Boundary Changes.....	9
Section 2.6 - Interpretation of District Boundaries.....	9
Section 2.7 – Submitting Model Backed Technical Data.....	9
Section 2.8 – Letters of Map Revision (LOMR)	10
ARTICLE III - ESTABLISHMENT OF FLOOD HAZARD DISTRICTS	11
Section 3.1 - Description of Special Flood Hazard Districts	11
Section 3.2 - Overlay Concept.....	12
ARTICLE IV - DISTRICT PROVISIONS.....	14
Section 4.1 – Permit and Application Requirements	14
Section 4.2 - General Standards.....	14
Section 4.3 - Elevation and Construction Standards.....	15
Section 4.4 - Standards for Subdivision Proposals	18
ARTICLE V – EXISTING STRUCTURES IN FLOODPLAIN AREAS	19
ARTICLE VI - NONCONFORMING STRUCTURES IN FLOODPLAIN AREAS.....	20
ARTICLE VII - VARIANCES: FACTORS TO BE CONSIDERED.....	21
ARTICLE VIII – ENACTMENT	23
GLOSSARY	24

ARTICLE I - GENERAL PROVISIONS

Section 1.1 – Statutory Authorization and Purpose [44 CFR 59.22(a) (2)]

This ordinance is adopted pursuant to the authority granted to localities by Va. Code § 15.2 - 2280.

The purpose of these provisions is to prevent: the loss of life and property, the creation of health and safety hazards, the disruption of commerce and governmental services, the extraordinary and unnecessary expenditure of public funds for flood protection and relief, and the impairment of the tax base by:

- A. regulating uses, activities, and development which, alone or in combination with other existing or future uses, activities, and development, will cause unacceptable increases in flood heights, velocities, and frequencies;
- B. restricting or prohibiting certain uses, activities, and development from locating within districts subject to flooding;
- C. requiring all those uses, activities, and developments that do occur in flood-prone districts to be protected and/or floodproofed against flooding and flood damage; and
- D. protecting individuals from buying land and structures which are unsuited for intended purposes because of flood hazards.

Section 1.2 – Applicability

These provisions shall apply to all privately- and publicly-owned lands within the jurisdiction of the Town of Gordonsville and identified as areas of special flood hazard shown on the flood insurance rate maps (FIRM) or included in the flood insurance study (FIS) that are provided to the Town of Gordonsville by FEMA.

Section 1.3 - Compliance and Liability

- A. No land shall hereafter be developed and no structure shall be located, relocated, constructed, reconstructed, enlarged, or structurally altered except in full compliance with the terms and provisions of this ordinance and any other applicable ordinances and regulations which apply to uses within the jurisdiction of this ordinance.
- B. The degree of flood protection sought by the provisions of this ordinance is considered reasonable for regulatory purposes and is based on acceptable engineering methods of study, but does not imply total flood protection. Larger floods may occur on rare occasions. Flood heights may be increased by man-made or natural causes, such as ice jams and bridge openings restricted by debris. This ordinance does not imply that districts outside the floodplain district or land uses permitted within such district will be free from flooding or flood damages.
- C. This ordinance shall not create liability on the part of the Town of Gordonsville or any officer or employee thereof for any flood damages that result from reliance on this ordinance or any administrative decision lawfully made thereunder.

Section 1.4 – Records [44 CFR 59.22(a)(9)(iii)]

Records of actions associated with administering this ordinance shall be kept on file and maintained by or under the direction of the Floodplain Administrator in perpetuity.

Section 1.5 - Abrogation and Greater Restrictions [44 CFR 60.1(b)]

To the extent that the provisions are more restrictive, this ordinance supersedes any ordinance currently in effect in flood-prone districts. To the extent that any other existing law or regulation is more restrictive or does not conflict it shall remain in full force and effect.

These regulations are not intended to repeal or abrogate any existing ordinances including subdivision regulations, zoning ordinances or building codes. In the event of a conflict between these regulations and any other ordinance, the more restrictive shall govern.

Section 1.6 - Severability

If any section, subsection, paragraph, sentence, clause, or phrase of this ordinance shall be declared invalid for any reason whatever, such decision shall not affect the remaining portions of this

ordinance. The remaining portions shall remain in full force and effect; and for this purpose, the provisions of this ordinance are hereby declared to be severable.

Section 1.7 - Penalty for Violations [44 CFR 60.2(e)]

Any person who fails to comply with any of the requirements or provisions of this article or directions of the Floodplain Administrator or designee shall be guilty of the appropriate violation and subject to the penalties as provided for in Section 1103 of the Town of Gordonsville Land Development Ordinance. The VA USBC addresses building code violations and associated penalties in Section 104 and Section 115.

In addition to the above penalties, all other actions are hereby reserved, including an action in equity for the proper enforcement of this article. The imposition of a fine or penalty for any violation of, or noncompliance with, this article shall not excuse the violation or noncompliance or permit it to continue; and all such persons shall be required to correct or remedy such violations within a reasonable time. Any structure constructed, reconstructed, enlarged, altered or relocated in noncompliance with this article may be declared by the Town of Gordonsville to be a public nuisance and abatable as such. Flood insurance may be withheld from structures constructed in violation of this article.

ARTICLE II - ADMINISTRATION

Section 2.1 - Designation of the Floodplain Administrator [44 CFR 59.22(b)]

The Town Manager or his/her designee is hereby appointed to administer and implement these regulations and is referred to herein as the Floodplain Administrator. The Floodplain Administrator may:

- A. Do the work themselves. In the absence of a designated Floodplain Administrator, the duties are conducted by the Town of Gordonsville Town Manager.
- B. Delegate duties and responsibilities set forth in these regulations to qualified technical personnel, plan examiners, inspectors, and other employees.
- C. Enter into a written agreement or written contract with another community or private sector entity to administer specific provisions of these regulations. Administration of any part of these regulations by another entity shall not relieve the community of its responsibilities pursuant to the participation requirements of the National Flood Insurance Program as set forth in the Code of Federal Regulations at 44 C.F.R. Section 59.22.

Section 2.2 - Duties and Responsibilities of the Floodplain Administrator [44 CFR 60.3]

The duties and responsibilities of the Floodplain Administrator shall include but are not limited to:

- A. Review applications for permits to determine whether proposed activities will be located in the Special Flood Hazard Area (SFHA).
- B. Interpret floodplain boundaries and provide available base flood elevation and flood hazard information.
- C. Review applications to determine whether proposed activities will be reasonably safe from flooding and require new construction and substantial improvements to meet the requirements of these regulations.
- D. Review applications to determine whether all necessary permits have been obtained from the Federal, State or local agencies from which prior or concurrent approval is required; in particular, permits from state agencies for any construction, reconstruction, repair, or alteration of a dam, reservoir, or waterway obstruction (including bridges, culverts, structures), any alteration of a watercourse, or any change of the course, current, or cross section of a stream or body of water, including any change to the 100-year frequency floodplain of free-flowing non-tidal waters of the State.
- E. Verify that applicants proposing an alteration of a watercourse have notified adjacent communities, the Department of Conservation and Recreation (Division of Dam Safety and Floodplain Management), and other appropriate agencies (Virginia Department of

Environmental Quality (VADEQ), United States Army Corps of Engineers (USACE) and have submitted copies of such notifications to FEMA.

- F. Approve applications and issue permits to develop in flood hazard areas if the provisions of these regulations have been met, or disapprove applications if the provisions of these regulations have not been met.
- G. Inspect or cause to be inspected, buildings, structures, and other development for which permits have been issued to determine compliance with these regulations or to determine if non-compliance has occurred or violations have been committed.
- H. Review Elevation Certificates and require incomplete or deficient certificates to be corrected.
- I. Submit to FEMA, or require applicants to submit to FEMA, data and information necessary to maintain FIRMs, including hydrologic and hydraulic engineering analyses prepared by or for the Town of Gordonsville within six months after such data and information becomes available if the analyses indicate changes in base flood elevations.
- J. Maintain and permanently keep records that are necessary for the administration of these regulations, including:
 - (1) Flood Insurance Studies, Flood Insurance Rate Maps (including historic studies and maps and current effective studies and maps) and Letters of Map Change; and
 - (2) Documentation supporting issuance and denial of permits, Elevation Certificates, documentation of the elevation (in relation to the datum on the FIRM) to which structures have been floodproofed, inspection records, other required design certifications, variances, and records of enforcement actions taken to correct violations of these regulations.
- K. Enforce the provisions of these regulations, investigate violations, issue notices of violations or stop work orders, and require permit holders to take corrective action.
- L. Advise the Board of Zoning Appeals regarding the intent of these regulations and, for each application for a variance, prepare a staff report and recommendation.
- M. Administer the requirements related to proposed work on existing buildings:
 - 1) Make determinations as to whether buildings and structures that are located in flood hazard areas and that are damaged by any cause have been substantially damaged.
 - 2) Make reasonable efforts to notify owners of substantially damaged structures of the need to obtain a permit to repair, rehabilitate, or reconstruct. Prohibit the non-compliant repair of substantially damaged buildings except for temporary emergency protective measures necessary to secure a property or stabilize a building or structure to prevent additional damage.

- N. Undertake, as determined appropriate by the Floodplain Administrator due to the circumstances, other actions which may include but are not limited to: issuing press releases, public service announcements, and other public information materials related to permit requests and repair of damaged structures; coordinating with other Federal, State, and local agencies to assist with substantial damage determinations; providing owners of damaged structures information related to the proper repair of damaged structures in special flood hazard areas; and assisting property owners with documentation necessary to file claims for Increased Cost of Compliance coverage under NFIP flood insurance policies.
- O. Notify the Federal Emergency Management Agency when the corporate boundaries of the Town of Gordonsville have been modified and:
 - (1) Provide a map that clearly delineates the new corporate boundaries or the new area for which the authority to regulate pursuant to these regulations has either been assumed or relinquished through annexation; and
 - (2) If the FIRM for any annexed area includes special flood hazard areas that have flood zones that have regulatory requirements that are not set forth in these regulations, prepare amendments to these regulations to adopt the FIRM and appropriate requirements, and submit the amendments to the governing body for adoption; such adoption shall take place at the same time as or prior to the date of annexation and a copy of the amended regulations shall be provided to Department of Conservation and Recreation (Division of Dam Safety and Floodplain Management) and FEMA.
- P. Upon the request of FEMA, complete and submit a report concerning participation in the NFIP which may request information regarding the number of buildings in the SFHA, number of permits issued for development in the SFHA, and number of variances issued for development in the SFHA.
- Q. It is the duty of the Community Floodplain Administrator to take into account flood, mudslide and flood-related erosion hazards, to the extent that they are known, in all official actions relating to land management and use throughout the entire jurisdictional area of the Community, whether or not those hazards have been specifically delineated geographically (e.g. via mapping or surveying).

Section 2.3 - Use and Interpretation of FIRMs [44 CFR 60.3]

The Floodplain Administrator shall make interpretations, where needed, as to the exact location of special flood hazard areas, floodplain boundaries, and floodway boundaries. The following shall apply to the use and interpretation of FIRMs and data:

- A. Where field surveyed topography indicates that adjacent ground elevations:

- (1) Are below the base flood elevation, even in areas not delineated as a special flood hazard area on a FIRM, the area shall be considered as special flood hazard area and subject to the requirements of these regulations;
 - (2) Are above the base flood elevation and the area is labeled as a SFHA on the FIRM, the area shall be regulated as special flood hazard area unless the applicant obtains a Letter of Map Change that removes the area from the SFHA.
- B. In FEMA-identified special flood hazard areas where base flood elevation and floodway data have not been identified and in areas where FEMA has not identified SFHAs, any other flood hazard data available from a Federal, State, or other source shall be reviewed and reasonably used.
- C. Base flood elevations and designated floodway boundaries on FIRMs and in FISs shall take precedence over base flood elevations and floodway boundaries by any other sources if such sources show reduced floodway widths and/or lower base flood elevations.
- D. Other sources of data shall be reasonably used if such sources show increased base flood elevations and/or larger floodway areas than are shown on FIRMs and in FISs.
- E. If a Preliminary Flood Insurance Rate Map and/or a Preliminary Flood Insurance Study has been provided by FEMA:
- (1) Upon the issuance of a Letter of Final Determination by FEMA, the preliminary flood hazard data shall be used and shall replace the flood hazard data previously provided from FEMA for the purposes of administering these regulations.
 - (2) Prior to the issuance of a Letter of Final Determination by FEMA, the use of preliminary flood hazard data shall be deemed the best available data pursuant to Section 3.1.A.3. and used where no base flood elevations and/or floodway areas are provided on the effective FIRM.
 - (3) Prior to issuance of a Letter of Final Determination by FEMA, the use of preliminary flood hazard data is permitted where the preliminary base flood elevations or floodway areas exceed the base flood elevations and/or designated floodway widths in existing flood hazard data provided by FEMA. Such preliminary data may be subject to change and/or appeal to FEMA.

Section 2.4 - Jurisdictional Boundary Changes [44 CFR 59.22, 65.3]

The County floodplain ordinance in effect on the date of annexation shall remain in effect and shall be enforced by the Town for all annexed areas until the Town shall pass a resolution acknowledging and accepting responsibility for enforcing floodplain ordinance standards prior to annexation of any area containing identified flood hazards. If the FIRM for any annexed area includes special flood hazard areas that have flood zones that have regulatory requirements that are not set forth in these regulations, prepare amendments to these regulations to adopt the FIRM

and appropriate requirements, and submit the amendments to the governing body for adoption; such adoption shall take place at the same time as or prior to the date of annexation and a copy of the amended regulations shall be provided to Department of Conservation and Recreation (Division of Dam Safety and Floodplain Management) and FEMA.

In accordance with the Code of Federal Regulations, Title 44 Subpart (B) Section 59.22 (a) (9) (v) all NFIP participating communities must notify the Federal Insurance Administration and optionally the State Coordinating Office in writing whenever the boundaries of the community have been modified by annexation or the community has otherwise assumed or no longer has authority to adopt and enforce floodplain management regulations for a particular area.

In order that all Flood Insurance Rate Maps accurately represent the community's boundaries, a copy of a map of the community suitable for reproduction, clearly delineating the new corporate limits or new area for which the community has assumed or relinquished floodplain management regulatory authority must be included with the notification.

Section 2.5 - District Boundary Changes

The delineation of any of the Floodplain Districts may be revised by the Town of Gordonsville where natural or man-made changes have occurred and/or where more detailed studies have been conducted or undertaken by the U. S. Army Corps of Engineers or other qualified agency, or an individual documents the need for such change. However, prior to any such change, approval must be obtained from the Federal Emergency Management Agency. A completed Letter of Map Revision (LOMR) is a record of this approval.

Section 2.6 - Interpretation of District Boundaries

Initial interpretations of the boundaries of the Floodplain Districts shall be made by the Zoning Officer. Should a dispute arise concerning the boundaries of any of the Districts, the Board of Zoning Appeals shall make the necessary determination. The person questioning or contesting the location of the District boundary shall be given a reasonable opportunity to present his case to the Board and to submit his own technical evidence if he so desires.

Section 2.7 – Submitting Model Backed Technical Data [44 CFR 65.3]

A community's base flood elevations may increase or decrease resulting from physical changes affecting flooding conditions. As soon as practicable, but not later than six months after the date such information becomes available, a community shall notify the Federal Emergency Management Agency of the changes by submitting technical or scientific data. The community may submit data via a LOMR. Such a submission is necessary so that upon confirmation of those physical changes affecting flooding conditions, risk premium rates and flood plain management requirements will be based upon current data.

Section 2.8 – Letters of Map Revision (LOMR)

When development in the floodplain will cause or causes a change in the base flood elevation, the applicant, including state agencies, must notify FEMA by applying for a Conditional Letter of Map Revision and then a Letter of Map Revision.

Example cases:

- Any development that causes a rise in the base flood elevations within the floodway.
- Alteration or relocation of a stream (including but not limited to installing culverts and bridges) *44 Code of Federal Regulations §65.3 and §65.6(a)(12)*

ARTICLE III - ESTABLISHMENT OF FLOOD HAZARD DISTRICTS

Section 3.1 - Description of Special Flood Hazard Districts [44 CFR 59.1, 60.3]

A. Basis of Districts

The various special flood hazard districts shall include the Special Flood Hazard Areas (SFHAs). The basis for the delineation of these districts shall be the FIS and the FIRM for the Town of Gordonsville prepared by the Federal Emergency Management Agency, Federal Insurance Administration, dated May 17, 2022, and any subsequent revisions or amendments thereto.

The Town of Gordonsville may identify and regulate local flood hazard or ponding areas that are not delineated on the FIRM. These areas may be delineated on a “Local Flood Hazard Map” using best available topographic data and locally derived information such as flood of record, historic high water marks or approximate study methodologies.

The boundaries of the SFHA Districts are established as shown on the FIRM which is declared to be a part of this ordinance and which shall be kept on file at the Town of Gordonsville offices. Provisions for the districts located within the Town are as follows:

1. The **A Zone** on the FIRM accompanying the FIS shall be those areas for which no detailed flood profiles or elevations are provided, but the one percent annual chance floodplain boundary has been approximated. For these areas, the following provisions shall apply [44 CFR 60.3(b)]:

The Approximated Floodplain District shall be that floodplain area for which no detailed flood profiles or elevations are provided, but where a one percent annual chance floodplain boundary has been approximated. Such areas are shown as Zone A on the maps accompanying the FIS. For these areas, the base flood elevations and floodway information from federal, state, and other acceptable sources shall be used, when available. Where the specific one percent annual chance flood elevation cannot be determined for this area using other sources of data, such as the U. S. Army Corps of Engineers Floodplain Information Reports, U. S. Geological Survey Flood-Prone Quadrangles, etc., then the applicant for the proposed use, development and/or activity shall determine this base flood elevation using methods that correctly reflect currently accepted practices, including but not limited to point on boundary, high water marks, or detailed hydrologic and hydraulic analyses. Studies, analyses, computations, etc., shall be submitted in sufficient detail to allow a thorough review by the Floodplain Administrator.

The Floodplain Administrator reserves the right to require a hydrologic and hydraulic analysis for any development.

During the permitting process, the Floodplain Administrator shall obtain:

- a) The elevation of the lowest floor (in relation to mean sea level), including the

basement, of all new and substantially improved structures; and,

- b) If the structure has been floodproofed in accordance with the requirements of this article, the elevation (in relation to mean sea level) to which the structure has been floodproofed.

Base flood elevation data shall be obtained from other sources or developed using detailed methodologies comparable to those contained in a FIS for subdivision proposals and other proposed development proposals (including manufactured home parks and subdivisions) that exceed five lots or five acres, whichever is the lesser.

2. The **AE Zone** on the FIRM accompanying the FIS shall be those areas for which one-percent annual chance flood elevations have been provided and the floodway has not been delineated. The following provisions shall apply within an AE zone [44 CFR 60.3(c)] where FEMA has provided base flood elevations:
 - a. Until a regulatory floodway is designated, no new construction, substantial improvements, or other development (including fill) shall be permitted within the areas of special flood hazard, designated as Zone AE on the FIRM, unless it is demonstrated that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one foot at any point within the Town.
 - b. Development activities in Zone AE on the Town's FIRM which increase the water surface elevation of the base flood by more than one foot may be allowed, provided that the applicant first applies – with the Town's endorsement – for a Conditional Letter of Map Revision, and receives the approval of the Federal Emergency Management Agency.
 - c. The Floodway District is in an AE Zone and is delineated, for purposes of this ordinance, using the criterion that certain areas within the floodplain must be capable of carrying the waters of the one percent annual chance flood without increasing the water surface elevation of that flood more than one (1) foot at any point. Gordonsville's current FIRM does not include any Floodway Districts.

Section 3.2 - Overlay Concept

The Floodplain Districts described above shall be overlays to the existing underlying districts as shown on the Official Zoning Ordinance Map, and as such, the provisions for the floodplain districts shall serve as a supplement to the underlying district provisions.

If there is any conflict between the provisions or requirements of the Floodplain Districts and those of any underlying district, the more restrictive provisions and/or those pertaining to the floodplain districts shall apply.

In the event any provision concerning a Floodplain District is declared inapplicable as a result of any legislative or administrative actions or judicial decision, the basic underlying provisions shall remain applicable.

ARTICLE IV - DISTRICT PROVISIONS [44 CFR 59.22, 60.2, 60.3]

Section 4.1 – Permit and Application Requirements

A. Permit Requirement

All uses, activities, and development occurring within any floodplain district, including placement of manufactured homes, shall be undertaken only upon the issuance of a zoning permit. Such development shall be undertaken only in strict compliance with the provisions of this Ordinance and with all other applicable codes and ordinances, as amended, such as the Virginia Uniform Statewide Building Code (VA USBC) and the Town of Gordonsville Subdivision Regulations. Prior to the issuance of any such permit, the Floodplain Administrator shall require all applications to include compliance with all applicable state and federal laws and shall review all sites to assure they are reasonably safe from flooding. Under no circumstances shall any use, activity, and/or development adversely affect the capacity of the channels or floodways of any watercourse, drainage ditch, or any other drainage facility or system.

B. Site Plans and Permit Applications

All applications for development within any floodplain district and all building permits issued for the floodplain shall incorporate the following information:

1. The elevation of the Base Flood at the site.
2. The elevation of the lowest floor (including basement).
3. For structures to be floodproofed (non-residential only), the elevation to which the structure will be floodproofed.
4. Topographic information showing existing and proposed ground elevations.

Section 4.2 - General Standards

The following provisions shall apply to all permits:

- A. New construction and substantial improvements shall be built according to this ordinance and the VA USBC, and anchored to prevent flotation, collapse or lateral movement of the structure.
- B. Manufactured homes shall be anchored to prevent flotation, collapse, or lateral movement. Methods of anchoring may include, but are not limited to, use of over-the-top or frame ties to ground anchors. This standard shall be in addition to and consistent with applicable state anchoring requirements for resisting wind forces.
- C. New construction and substantial improvements shall be constructed with materials and utility equipment resistant to flood damage.

- D. New construction or substantial improvements shall be constructed by methods and practices that minimize flood damage.
- E. Electrical, heating, ventilation, plumbing, air conditioning equipment and other service facilities, including duct work, shall be designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding.
- F. New and replacement water supply systems shall be designed to minimize or eliminate infiltration of flood waters into the system.
- G. New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of flood waters into the systems and discharges from the systems into flood waters.
- H. On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding.

In addition to provisions A – H above, in all special flood hazard areas, the additional provisions shall apply:

1. Prior to any proposed alteration or relocation of any channels or of any watercourse, stream, etc., within this jurisdiction a permit shall be obtained from the U. S. Corps of Engineers, the Virginia Department of Environmental Quality, and the Virginia Marine Resources Commission (a joint permit application is available from any of these organizations). Furthermore, in riverine areas, notification of the proposal shall be given by the applicant to all affected adjacent jurisdictions, the Department of Conservation and Recreation (Division of Dam Safety and Floodplain Management), other required agencies, and the Federal Emergency Management Agency.
2. The flood carrying capacity within an altered or relocated portion of any watercourse shall be maintained.

Section 4.3 - Elevation and Construction Standards [44 CFR 60.3]

In all identified flood hazard areas, the following provisions shall apply:

A. Residential Construction

New construction or substantial improvement of any residential structure (including manufactured homes) in Zones A and AE shall have the lowest floor, including basement, elevated to or above the base flood elevation *plus eighteen (18) inches*.

B. Non-Residential Construction

1. New construction or substantial improvement of any commercial, industrial, or non-residential building (or manufactured home) within Zones A and AE shall have the lowest floor, including basement, elevated to or above the base flood level plus *eighteen (18) inches*; OR, together with attendant utility and sanitary facilities, be designed so that below the base flood level the structure is watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads and effects of buoyancy;”.
2. Where a non-residential structure is intended to be made watertight below the base flood level, (i) a registered professional engineer or architect shall develop and/or review structural design, specifications, and plans for the construction, and shall certify that the design and methods of construction are in accordance with accepted standards of practice for meeting the applicable provisions of paragraph (c)(3) of this section, and (ii) a record of such certificates which includes the specific elevation (in relation to mean sea level) to which such structures are floodproofed shall be maintained with the official designated by the community under § 59.22(a)(9)(iii).

C. Space Below the Lowest Floor

In zone A, fully enclosed areas, of new construction or substantially improved structures, which are below the regulatory flood protection elevation shall:

1. Not be designed or used for human habitation, but shall be used solely for parking of vehicles, building access, or limited storage of maintenance equipment used in connection with the premises. Access to the enclosed area shall be the minimum necessary to allow for parking of vehicles (garage door) or limited storage of maintenance equipment (standard exterior door), or entry to the living area (stairway or elevator).
2. be constructed entirely of flood resistant materials below the regulatory flood protection elevation;
3. include measures to automatically equalize hydrostatic flood forces on walls by allowing for the entry and exit of floodwaters. To meet this requirement, the openings must either be certified by a professional engineer or architect or meet the following minimum design criteria:
 - a. Provide a minimum of two openings on different sides of each enclosed area subject to flooding.
 - b. The total net area of all openings must be at least one (1) square inch for each square foot of enclosed area subject to flooding.
 - c. If a building has more than one enclosed area, each area must have openings to allow floodwaters to automatically enter and exit.

- d. The bottom of all required openings shall be no higher than one (1) foot above the adjacent grade.
- e. Openings may be equipped with screens, louvers, or other opening coverings or devices, provided they permit the automatic flow of floodwaters in both directions.
- f. Foundation enclosures made of flexible skirting are not considered enclosures for regulatory purposes, and, therefore, do not require openings. Masonry or wood underpinning, regardless of structural status, is considered an enclosure and requires openings as outlined above.

D. Standards for Manufactured Homes and Recreational Vehicles

In zone A, all manufactured homes placed, or substantially improved, on individual lots or parcels, must meet all the requirements for new construction, including the elevation and anchoring requirements in section 4.2.

E. Accessory Structures

- 1. Accessory structures in the SFHA shall comply with the elevation requirements and other requirements of Article IV, Section 4.3.B or, if not elevated or dry floodproofed, shall:
 - a. Not be used for human habitation;
 - b. Be limited to no more than *600 square feet* in total floor area;
 - c. Be useable only for parking of vehicles or limited storage;
 - d. Be constructed with flood damage-resistant materials below the base flood elevation;
 - e. Be constructed and placed to offer the minimum resistance to the flow of floodwaters;
 - f. Be anchored to prevent flotation;
 - g. Have electrical service and mechanical equipment elevated to or above the base flood elevation;
 - h. Shall be provided with flood openings which shall meet the following criteria:
 - (1) There shall be a minimum of two flood openings on different sides of each enclosed area; if a building has more than one enclosure below the lowest floor, each such enclosure shall have flood openings on exterior walls.

- (2) The total net area of all flood openings shall be at least 1 square inch for each square foot of enclosed area (non-engineered flood openings), or the flood openings shall be engineered flood openings that are designed and certified by a licensed professional engineer to automatically allow entry and exit of floodwaters; the certification requirement may be satisfied by an individual certification or an Evaluation Report issued by the ICC Evaluation Service, Inc.
- (3) The bottom of each flood opening shall be one (1) foot or less above the higher of the interior floor or grade, or the exterior grade, immediately below the opening.
- (4) Any louvers, screens or other covers for the flood openings shall allow the automatic flow of floodwaters into and out of the enclosed area.
 - i. A signed Declaration of Land Restriction (Non-Conversion Agreement) shall be recorded on the property deed.

Section 4.4 - Standards for Subdivision Proposals

- A. All subdivision proposals shall be consistent with the need to minimize flood damage;
- B. All subdivision proposals shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize flood damage;
- C. All subdivision proposals shall have adequate drainage provided to reduce exposure to flood hazards, and
- D. Base flood elevation data shall be obtained from other sources or developed using detailed methodologies, hydraulic and hydrologic analysis, comparable to those contained in a Flood Insurance Study for subdivision proposals and other proposed development proposals (including manufactured home parks and subdivisions) that exceed five lots or five acres, whichever is the lesser.

ARTICLE V – EXISTING STRUCTURES IN FLOODPLAIN AREAS

Any structure or use of a structure or premises must be brought into conformity with these provisions when it is changed, repaired, or improved unless one of the following exceptions is established before the change is made:

- A. The floodplain manager has determined that:
 - 1. change is not a substantial repair or substantial improvement; and
 - 2. no new square footage is being built in the floodplain that is not compliant; and
 - 3. no new square footage is being built in the floodway; and
 - 4. the change complies with this ordinance and the VA USBC; and
 - 5. the change, when added to all the changes made during a rolling 5 year period, does not constitute 50% of the structure's value.
- B. The changes are required to comply with a citation for a health or safety violation.
- C. The structure is a historic structure and the change required would impair the historic nature of the structure.

ARTICLE VI – NONCONFORMING STRUCTURES IN FLOODPLAIN AREAS

Any pre-FIRM structure which lawfully existed before (*date of ordinance amendment to include the floodplain ordinance in the LDO*), but which is not in conformity with the requirements of the flood hazard overlay district, may continue, subject to the following:

- A. Expansion or enlargement of existing structures. Existing structures shall not be expanded or enlarged.
- B. Modification, alteration, repair, reconstruction or improvement of an existing structure; not a substantial improvement. Existing structures may be modified, altered, repaired, reconstructed or improved (collectively, the “improvements”), but not enlarged or expanded, where the improvements are not a substantial improvement, provided that the improvements: (i) are authorized by section 707, as applicable; and (ii) comply with the Virginia Uniform Statewide Building Code.
- C. Modification, alteration, repair, reconstruction or improvement of an existing structure; substantial improvement. Existing structures may be modified, altered, repaired, reconstructed or improved (the “improvements”), where the improvements qualify as a substantial improvement, provided that: (i) the entire structure complies with the requirements of the flood hazard overlay district and all other applicable laws; and (ii) the entire structure complies with the Virginia Uniform Statewide Building Code.
- D. Repair or rehabilitation of historic structure; substantial improvement. Any historic structure undergoing repair or rehabilitation that would constitute a substantial improvement shall comply with any requirements of the flood hazard overlay district that do not preclude the structure’s continued designation as a historic structure. The owner shall provide documentation from the Secretary of the Interior or the State Historic Preservation Officer that a specific requirement of the flood hazard overlay district will cause removal of the structure from the National Register of Historic Places or the State Inventory of Historic places, as applicable. Any relief from any requirement shall be the minimum necessary to preserve the historic character and design of the structure.

ARTICLE VII - VARIANCES: FACTORS TO BE CONSIDERED [44 CFR 60.6]

Variations shall be issued only (i) upon a showing of good and sufficient cause, (ii) after the Board of Zoning Appeals has determined that failure to grant the variance would result in exceptional hardship to the applicant, and (iii) after the Board of Zoning Appeals has determined that the granting of such variance will not result in (a) unacceptable or prohibited increases in flood heights, (b) additional threats to public safety, (c) extraordinary public expense; and will not (d) create nuisances, (e) cause fraud or victimization of the public, or (f) conflict with local laws or ordinances.

Variations may be issued for new construction and substantial improvements and for other development necessary for the conduct of a functionally dependent use provided that the criteria of this section are met, and the structure or other development is protected by methods that minimize flood damages during the base flood and create no additional threats to public safety.

In passing upon applications for variations, the Board of Zoning Appeals shall satisfy all relevant factors and procedures specified in other sections of the zoning ordinance and consider the following additional factors:

- A. The danger to life and property due to increased flood heights or velocities caused by encroachments. No variance shall be granted for any proposed use, development, or activity within any Floodway District that will cause any increase in the one percent (1%) chance flood elevation.
- B. The danger that materials may be swept on to other lands or downstream to the injury of others.
- C. The proposed water supply and sanitation systems and the ability of these systems to prevent disease, contamination, and unsanitary conditions.
- D. The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owners.
- E. The importance of the services provided by the proposed facility to the community.
- F. The requirements of the facility for a waterfront location.
- G. The availability of alternative locations not subject to flooding for the proposed use.
- H. The compatibility of the proposed use with existing development and development anticipated in the foreseeable future.
- I. The relationship of the proposed use to the comprehensive plan and floodplain management program for the area.
- J. The safety of access by ordinary and emergency vehicles to the property in time of flood.

- K. The expected heights, velocity, duration, rate of rise, and sediment transport of the flood waters expected at the site.
- L. The historic nature of a structure. Variances for repair or rehabilitation of historic structures may be granted upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure and the variance is the minimum necessary to preserve the historic character and design of the structure.
- M. Such other factors which are relevant to the purposes of this ordinance.
- N. No variance shall be granted for an accessory structure exceeding 600 square feet. (*Note: See Article IV, Section 4.3.E.2).*)

The Board of Zoning Appeals may refer any application and accompanying documentation pertaining to any request for a variance to any engineer or other qualified person or agency for technical assistance in evaluating the proposed project in relation to flood heights and velocities, and the adequacy of the plans for flood protection and other related matters.

Variances shall be issued only after the Board of Zoning Appeals has determined that the granting of such will not result in (a) unacceptable or prohibited increases in flood heights, (b) additional threats to public safety, (c) extraordinary public expense; and will not (d) create nuisances, (e) cause fraud or victimization of the public, or (f) conflict with local laws or ordinances.

Variances shall be issued only after the Board of Zoning Appeals has determined that the variance will be the minimum required to provide relief.

The Board of Zoning Appeals shall notify the applicant for a variance, in writing that the issuance of a variance to construct a structure below the one percent (1%) chance flood elevation (a) increases the risks to life and property and (b) will result in increased premium rates for flood insurance.

A record shall be maintained of the above notification as well as all variance actions, including justification for the issuance of the variances. Any variances that are issued shall be noted in the annual or biennial report submitted to the Federal Insurance Administrator.

ARTICLE VIII – ENACTMENT

Enacted and ordained this 16th day of August, 2016. This ordinance of the Town of Gordonsville, Virginia, shall become effective upon passage.

Signature

Title

Attested

GLOSSARY [44 CFR 59.1]

1. Appurtenant or accessory structure - A non-residential structure which is on the same parcel of property as the principal structure and the use of which is incidental to the use of the principal structure. Accessory structures are not to exceed *600 square feet*.
2. Base flood - The flood having a one percent chance of being equalled or exceeded in any given year.
3. Base flood elevation - The water surface elevations of the base flood, that is, the flood level that has a one percent or greater chance of occurrence in any given year. The water surface elevation of the base flood in relation to the datum specified on the community's Flood Insurance Rate Map. For the purposes of this ordinance, the base flood is the 1% annual chance flood.
4. Basement - Any area of the building having its floor sub-grade (below ground level) on all sides.
5. Board of Zoning Appeals - The board appointed to review appeals made by individuals with regard to decisions of the Zoning Administrator in the interpretation of this ordinance.
6. Development - Any man-made change to improved or unimproved real estate, including, but not limited to, buildings or other structures, mining, dredging, filling, grading, paving, excavation or drilling operations or storage of equipment or materials.
7. Elevated building - A non-basement building built to have the lowest floor elevated above the ground level by means of solid foundation perimeter walls, pilings, or columns (posts and piers).
8. Encroachment - The advance or infringement of uses, plant growth, fill, excavation, buildings, permanent structures or development into a floodplain, which may impede or alter the flow capacity of a floodplain.
9. Existing construction – For the purposes of the insurance program, structures for which the “start of construction” commenced before the effective date of the FIRM or before January 1, 1975 for FIRMs effective before that date. “Existing construction” may also be referred to as “existing structures” and “pre-FIRM.”
10. Flood or flooding -
 - a. A general or temporary condition of partial or complete inundation of normally dry land areas from:
 1. the overflow of inland or tidal waters; or,
 2. the unusual and rapid accumulation or runoff of surface waters from any source.
 3. mudflows which are proximately caused by flooding as defined in paragraph (1)(b) of this definition and are akin to a river of liquid and flowing mud on the surfaces

of normally dry land areas, as when earth is carried by a current of water and deposited along the path of the current.

- b. The collapse or subsidence of land along the shore of a lake or other body of water as a result of erosion or undermining caused by waves or currents of water exceeding anticipated cyclical levels or suddenly caused by an unusually high water level in a natural body of water, accompanied by a severe storm, or by an unanticipated force of nature such as flash flood or an abnormal tidal surge, or by some similarly unusual and unforeseeable event which results in flooding as defined in paragraph 1 (a) of this definition.
11. Flood Insurance Rate Map (FIRM) - an official map of a community, on which the Federal Emergency Management Agency has delineated both the special hazard areas and the risk premium zones applicable to the community. A FIRM that has been made available digitally is called a Digital Flood Insurance Rate Map (DFIRM).
12. Flood Insurance Study (FIS) – a report by FEMA that examines, evaluates and determines flood hazards and, if appropriate, corresponding water surface elevations, or an examination, evaluation and determination of mudflow and/or flood-related erosion hazards.
13. Floodplain or flood-prone area - Any land area susceptible to being inundated by water from any source.
14. Floodproofing - any combination of structural and non-structural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, structures and their contents.
15. Floodway - The channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one foot at any point within the community.
16. Freeboard - A factor of safety usually expressed in feet above a flood level for purposes of floodplain management. “Freeboard” tends to compensate for the many unknown factors that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions, such as wave action, bridge openings, and the hydrological effect of urbanization in the watershed.
17. Habitable space - An enclosed area having more than twenty (20) linear feet of finished walls composed of, but not limited to, drywall, paneling, lath and plaster, or used for any purpose other than solely for parking of vehicles, building access, or storage.
18. Highest adjacent grade - the highest natural elevation of the ground surface prior to construction next to the proposed walls of a structure.
19. Historic structure - Any structure that is:
 1. listed individually in the National Register of Historic Places (a listing maintained by

- the Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
2. certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district;
 3. individually listed on a state inventory of historic places in states with historic preservation programs which have been approved by the Secretary of the Interior; or,
 4. individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either
 - a. by an approved state program as determined by the Secretary of the Interior; or,
 - b. directly by the Secretary of the Interior in states without approved programs.
20. Hydrologic and Hydraulic Engineering Analysis – Analyses performed by a *licensed* professional engineer, in accordance with standard engineering practices that are accepted by the Virginia Department of Conservation and Recreation and FEMA, used to determine the *base flood*, other frequency floods, *flood* elevations, *floodway* information and boundaries, and *flood* profiles.
21. Letter of Map Change (LOMC) - A Letter of Map Change is an official FEMA determination, by letter, that amends or revises an effective *Flood Insurance Rate Map* or *Flood Insurance Study*. Letter of Map Change includes:
- a. Letter of Map Amendment (LOMA): An amendment based on technical data showing that a property was incorrectly included in a designated *special flood hazard area*. A LOMA amends the current effective *Flood Insurance Rate Map* and establishes that a land as defined by meets and bounds or *structure* is not located in a *special flood hazard area*.
 - b. Letter of Map Revision (LOMR): A revision based on technical data that may show changes to *flood zones*, *flood* elevations, *floodplain* and *floodway* delineations, and planimetric features. A Letter of Map Revision Based on Fill (LOMR-F), is a determination that a *structure* or parcel of land has been elevated by fill above the *base flood elevation* and is, therefore, no longer exposed to *flooding* associated with the *base flood*. In order to qualify for this determination, the fill must have been permitted and placed in accordance with the *community's* floodplain management regulations.
 - c. Conditional Letter of Map Revision (CLOMR): A formal review and comment as to whether a proposed *flood* protection project or other project complies with the minimum NFIP requirements for such projects with respect to delineation of *special flood hazard areas*. A CLOMR does not revise the effective *Flood Insurance Rate Map* or *Flood Insurance Study*.
22. Lowest adjacent grade - the lowest natural elevation of the ground surface next to the walls of a structure.

23. Lowest floor - The lowest floor of the lowest enclosed area (including basement). An unfinished or flood-resistant enclosure, usable solely for parking of vehicles, building access or storage in an area other than a basement area is not considered a building's lowest floor; provided, that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements of Federal Code 44CFR §60.3.
24. Manufactured home - A structure, transportable in one or more sections, which is built on a permanent chassis and is designed for use with or without a permanent foundation when connected to the required utilities. For floodplain management purposes the term "manufactured home" also includes park trailers, travel trailers, and other similar vehicles placed on a site for greater than 180 consecutive days.
25. Manufactured home park or subdivision - a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.
26. Mean Sea Level – is an elevation point that represents the average height of the ocean's surface (such as the halfway point between the mean high tide and the mean low tide) which is used as a standard in reckoning land elevation.
27. New construction - For the purposes of determining insurance rates, structures for which the "start of construction" commenced on or after January 2, 2008, and includes any subsequent improvements to such structures. For floodplain management purposes, *new construction* means structures for which the *start of construction* commenced on or after the effective date of a floodplain management regulation adopted by a community and includes any subsequent improvements to such structures.
28. Post-FIRM structures - A structure for which construction or substantial improvement occurred on or after January 2, 2008.
29. Pre-FIRM structures - A structure for which construction or substantial improvement occurred on or before January 2, 2008.
30. Recreational vehicle - A vehicle which is:
 1. built on a single chassis;
 2. 400 square feet or less when measured at the largest horizontal projection;
 3. designed to be self-propelled or permanently towable by a light duty truck; and,
 4. designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational camping, travel, or seasonal use.
31. Repetitive Loss Structure – A building covered by a contract for flood insurance that has incurred flood-related damages on two occasions in a 10-year period, in which the cost of the repair, on the average, equalled or exceeded 25 percent of the market value of the structure at the time of each such flood event; and at the time of the second incidence of flood-related damage, the contract for flood insurance contains increased cost of compliance coverage.
32. Severe repetitive loss structure - a structure that: (a) Is covered under a contract for flood

insurance made available under the NFIP; and (b) Has incurred flood related damage – (i) For which 4 or more separate claims payments have been made under flood insurance coverage with the amount of each such claim exceeding \$5,000, and with the cumulative amount of such claims payments exceeding \$20,000; or (ii) For which at least 2 separate claims payments have been made under such coverage, with the cumulative amount of such claims exceeding the market value of the insured structure.

33. Shallow flooding area – A special flood hazard area with base flood depths from one to three feet where a clearly defined channel does not exist, where the path of flooding is unpredictable and indeterminate, and where velocity flow may be evident. Such flooding is characterized by ponding or sheet flow.
34. Special flood hazard area - The land in the floodplain subject to a one (1%) percent or greater chance of being flooded in any given year as determined in Article 3, Section 3.1 of this ordinance.
35. Start of construction - For other than new construction and substantial improvement, under the Coastal Barriers Resource Act (P.L. – 97-348), means the date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, substantial improvement or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for a basement, footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of the construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.
36. Structure - for floodplain management purposes, a walled and roofed building, including a gas or liquid storage tank, that is principally above ground, as well as a manufactured home.
37. Substantial damage - Damage of any origin sustained by a structure whereby the cost of restoring the structure to its before-damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred.
38. Substantial improvement - Any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent of the market value of the structure before the *start of construction* of the improvement. The term does not, however, include either:
 - a. any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by

- the local code enforcement official and which are the minimum necessary to assure safe living conditions; or
- b. any alteration of a *historic structure*, provided that the alteration will not preclude the structure's continued designation as a *historic structure*.

Historic structures undergoing repair or rehabilitation that would constitute a substantial improvement as defined above must comply with all ordinance requirements that do not preclude the structure's continued designation as a historic structure. Documentation that a specific ordinance requirement will cause removal of the structure from the National Register of Historic Places or the State Inventory of Historic places must be obtained from the Secretary of the Interior or the State Historic Preservation Officer. Any exemption from ordinance requirements will be the minimum necessary to preserve the historic character and design of the structure.

39. Violation - the failure of a structure or other development to be fully compliant with the community's floodplain management regulations. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required in this ordinance is presumed to be in violation until such time as that documentation is provided.
40. Watercourse - A lake, river, creek, stream, wash, channel or other topographic feature on or over which waters flow at least periodically. Watercourse includes specifically designated areas in which substantial flood damage may occur.
41. Zone A - A special flood hazard area that is subject to inundation by the one (1) percent annual chance flood event (one hundred year flood) where detailed hydraulic analyses have not been performed and no base flood elevations or flood depths are shown.